

CLAMP METERS

UT200B+

- AC Current: 600A
- DC Voltage: 600 V
- AC Voltage: 600V
- Frequency: 10H ~ 10kHz
- Resistance: 30kΩ
- Capacitance: 300μF
- Auto Range
- Jaw Capacity 28mm
- Diode
- Continuity Buzzer
- Low Battery Indication
- Data Hold
- LCD Backlight
- Flashlight
- High Voltage Warning
- 3099 Display Count



R622.¹⁵
R541.⁰⁰ excl VAT

UT201+ 400A

- AC Current: 400A
- AC/DC Voltage: 600V
- Resistance: 40MΩ
- Display Size: 35 x 27mm
- Backlight
- NCV
- MAX/MIN
- Auto Ranging
- Data Hold
- Diode
- Continuity Test
- Low Voltage Indicator
- Jaw Capacity 28mm
- APO
- 4000 Display Count



R756.⁷⁰
R658.⁰⁰ excl VAT

UT203+ 400A

- AC/DC Current: 40/400A
- AC/DC Voltage: 600V
- Resistance: 40MΩ
- Capacitance: 10mF
- Frequency: 10MHz
- NCV
- Diode Test
- Continuity Buzzer
- Data Hold
- Low Battery Indication
- Jaw Capacity 28mm
- Relative Mode
- Display Size: 35 x 27mm
- 4000 Display Count
- Duty Cycle
- APO
- Backlight
- Auto Range
- MAX/MIN



R1557.¹⁰
R1354.⁰⁰ excl VAT

UT206A+

- AC Current: 1000A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 45Hz ~ 1kHz
- Temperature: -40°C ~ 1000°C
- Jaw Capacity > 40mm
- Inrush Current: 1000A
- Auto Range
- NCV
- MAX/MIN/REL
- Continuity Buzzer
- Low Battery Indication
- 6000 Display Count
- Diode
- Data Hold
- LCD Backlight
- APO



R1509.³⁹
R1312.⁵¹ excl VAT

UT211B

- AC/DC Current: 60A
- AC/DC Voltage: 600V
- Resistance: 60MΩ
- Frequency: 60kHz
- Capacitance: 62mF
- Continuity Buzzer
- Resolution: 0.1mA
- Jaw Capacity 17mm
- NCV
- ZERO Mode
- Data Hold
- LCD Backlight
- APO
- V.F.C.
- Diode
- Low Battery Indication
- Input Protection
- Ideal for Solar Power Systems
- 6000 Display Count



R3633.²⁶
R3159.³⁶ excl VAT

UT208B

- AC/DC Current: 1000A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 10Hz ~ 1MHz
- Temperature: -40°C ~ 1000°C
- Auto Range
- Jaw Capacity 42mm
- Diode
- Inrush Current
- Data Hold
- NCV
- MAX/MIN/REL
- LCD Backlight
- Flashlight
- Continuity Buzzer
- Low Battery Indication
- Overload Indication
- High Voltage Warning
- 6000 Display Count



R3240.⁵³
R2817.⁹⁵ excl VAT

UT256B

- AC/DC Current: 200A
- DC Voltage: 1000 V
- AC Voltage: 750V
- Resistance: 60MΩ
- Capacitance: 60mF
- Auto Ranging
- Diode
- Data Hold
- LCD Backlight
- APO
- Continuity Buzzer
- Input Protection
- Low Battery Indication
- Relative Mode
- 6000 Display Count
- NCV
- Zero Mode



R924.⁹⁸
R804.³³ excl VAT

MULTIMETERS

Palm Size Multimeter

UT33D+

- AC/DC Voltage: 600 V
- DC Current: 10A
- Resistance: 20MΩ
- NCV
- APO



R351.⁵⁷

R305.⁷¹ excl VAT

Pocket Size Household True RMS Multimeter

UT123D

- AC/DC Voltage: 600V
- AC/DC Current: 10A
- Resistance: 40MΩ
- Capacitance: 400μF
- Acousto-optic Indication
- Data Hold



R664.⁷⁰

R578.⁰⁰ excl VAT

True RMS Multimeter

UT60EU

- AC/DC Voltage: 1000 V
- AC/DC Current: 10A
- Resistance: 100MΩ
- Capacitance: 10mF
- Frequency: 99.99Hz ~ 9.999MHz
- Duty Cycle: 0.1~99.9%
- Temperature: -40°C ~ 1000°C



R803.⁸⁵

R699.⁰⁰ excl VAT

Pocket Size Multimeter

UT120B

- AC/DC Voltage: 600V
- Resistance: 40MΩ
- Capacitance: 100μF
- Frequency: 10MHz
- Duty Cycle
- Data Hold



R587.⁵⁹

R510.⁹⁵ excl VAT

Smart Digital Multimeter

UT122

- AC Voltage: 750V
- DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 99.99mF
- Frequency: 10Hz ~ 10MHz



R897.⁷⁸

R780.⁸⁸ excl VAT

True RMS Multimeter

UT61D+

- AC/DC Voltage: 1000 V
- AC/DC Current: 20A
- Resistance: 60MΩ
- Frequency: 10Hz ~ 10MHz
- Capacitance: 60mF
- Temperature: -40°C ~ 1000°C
- MAX/MIN



R1774.⁴⁵

R1543.⁰⁰ excl VAT

Pocket Size Multimeter

UT125C

- AC/DC Voltage: 600V
- AC/DC Current: 400mA
- Resistance: 40MΩ
- Frequency: 60kHz
- Capacitance: 100μF
- Diode



R700.³⁵

R609.⁰⁰ excl VAT

Smart Digital Multimeter

UT121A

- AC/DC Voltage: 600V
- Resistance: 10MΩ
- Temperature: -40°C ~ 1000°C
- Dual Display
- Auto Range
- NCV



R485.³⁰

R422.⁰⁰ excl VAT

TRMS Multimeter

UT89X

- AC/DC Voltage: 1000 V
- AC/DC Current: 20A
- Resistance: 60MΩ
- Capacitance: 100mF
- Frequency: 10MHz
- Continuity Buzzer
- Diode



R786.⁶⁸

R684.⁰⁷ excl VAT

TESTERS & METERS

Laser Distance Meter

LM70A

- Range: 70m
- Measurement Units: m/ft/in
- Min. Display Unit: 0.001m
- Measurement Basis: Front/Rear
- Accuracy: +/- 2mm
- Laser Class: 2
- Laser Type: 630 ~ 670nm, <1mW
- Single Measurement
- Continuous Measurement
- MAX/MIN/AREA



R986.⁷⁰

R858.⁰⁰ excl VAT

400° C Infrared Thermometer

UT300S

- Temperature: -32 ~ 400°C
- Accuracy +/- 2°C
- Distance To Spot Ratio: 12:1
- Response Time 500ms
- Emissivity 0.10 ~ 1.00 Adjustable
- Selection °C/°F
- Display Hold
- APO
- Low Battery Indication



R483.⁰⁰

R420.⁰⁰ excl VAT

200A TRMS Fork Meter

UT256A

- AC Current: 200A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 10 ~ 10kHz
- Auto Range
- Data Hold
- NCV
- LCD Backlight



R1589.⁴⁵

R1382.¹³ excl VAT

5.5GΩ Insulation Resistance Tester

- Test Voltage 100/250/500/1000V
- Insulation Resistance (Ω) 5.5GΩ
- Short Circuit Current: <2mA
- AC Voltage (V) 750V
- Auto Range
- Low Battery Indication
- LCD Backlight
- Alarm Indication
- Alarm Buzzer
- High Voltage Indication
- Overload Indication
- Auto Discharge
- 10mΩ Internal Resistance Test
- 2000 Display Count



R1896.³⁵

R1649.⁰⁰ excl VAT

Compliance Tester Multi-Functional

- AC Voltage: 440V
- DC Voltage: 440V
- Insulation Test: 250/500/1000V
- Phase Rotation
- Prospective Short Circuit: 26kA
- RCD Test Current: 10/30/100/300/500mA
- Low Ohm Measurement
- Loop Impedance
- ELCB Test (Time & Sensitivity)
- APO
- LCD Backlight
- Low Battery Indication
- Phase Switch (RCD) 0 ~ 180°
- Data Logging



R14523.³⁵

R12629.⁰⁰ excl VAT

Earth Ground Tester

- Earth Resistance: 0 ~ 4000Ω
- AC Earth Voltage: 0 ~ 400V
- Manual Range
- APO
- Low Battery Indication
- Data Hold
- Data Storage 20
- LCD Backlight
- Full Icon Display
- Double Insulation Protection
- Contact Badness Indication
- Simple 2-Wire Testing
- Precision 3-Wire Testing
- Over-Range Display
- 4000 Display Count



R5635.⁰⁰

R4900.⁰⁰ excl VAT

Temperature Humidity Meter

- Temperature: -10 ~ 50°C
- Sampling Time: 10s
- Display of Temperature, Humidity and Time
- Dual Temperature Measurement
- Humidity: 20% ~ 95% RH
- External Temperature: -10°C ~ 50°C
- MAX/MIN
- Comfort Rating: Cold/Dry/Comfort
- Alarm Clock/Time Display
- 12/24 Hour Mode



R350.⁷⁵

R305.⁰⁰ excl VAT

JOHANNESBURG

Tel: +27 11 392 3804

DURBAN

Tel: +27 31 263 7800

CAPE TOWN

Tel: +27 21 552 5242